



Installation instructions

# **HOLDER FOR SIDE BAG**

**MAKE LIFE A RIDE** 

04/2025

# BEFORE COMMENCING WORK, YOU MUST READ THESE INSTALLATION INSTRUCTIONS THROUGH CAREFULLY AND MAKE SURE YOU UNDERSTAND THEM FULLY.

We congratulate you on your choice of optional accessories from BMW Motorrad that will enable you to customise your motorcycle in accordance with your personal preferences.

Safety is invariably an essential prerequisite for extracting full benefit and enjoyment from new accessories. Some work calls for special tools and possibly a thorough knowledge of motorcycle technology. If you are in doubt consult a specialist workshop, preferably your authorised BMW Motorrad dealer.

Since we provide you with a multitude of accessories and optional equipment, we cannot cover all equipment specifications in these installation instructions. Therefore we restrict ourselves to the basic version of the corresponding model. The removal and installation of other possibly installed accessories is described in the corresponding installation instructions. Consult your authorised BMW Motorrad dealer if you no longer have access to the sets of instructions you need.

If you have questions concerning your motorcycle or any of the accessories from our range, your authorised BMW Motorrad dealer will gladly provide advice and assistance.

We at BMW Motorrad hope you will enjoy riding your BMW and that all your journeys will be pleasant and safe.

# THE SYMBOLS USED TO DRAW ATTENTION TO PRECAUTIONARY STATEMENTS IN THIS MANUAL ARE AS FOLLOWS:



Low-risk hazard. Non-avoidance can lead to slight or moderate injury.

# **⚠** DANGER

High-risk hazard. Non-avoidance leads to fatal or severe injury.

# NOTICE

Specific instructions on how to operate, control, adjust or look after items of equipment on the motorcycle.

- Start of the main activity
- Start of the secondary activity
- Instruction

# **!** WARNING

Medium-risk hazard. Non-avoidance can lead to fatal or severe injury.

# **ATTENTION**

Special notes and precautionary measures. Non-compliance can lead to damage to the vehicle or accessory and, consequently, to voiding of the warranty.

# Tightening torque

Screws, bolts and nuts are tightened in accordance with the applicable DIN/ISO standards. Tightening torques that deviate from the standards are stated. Non-compliance can result in damage to the vehicle or accessories or can endanger the driver.

- End of the main activity
- ☐ End of the secondary activity
- End of validity designation CS (construction status), OE (optional extra) or OA (optional accessory)

© 2025 Bayerische Motoren Werke Aktiengesellschaft 80788 Munich, Germany

Not to be reproduced by any means whatsoever, wholly or in part, without the written permission of BMW Motorrad, Aftersales.

Printed in Germany.

Subject to change without notice. Errors and omissions excepted.

All rights reserved.

# Holder for side bag

#### Requisite tools

- Torx wrench set
- Torque wrench



### Scope of installation

- Side bag holder kit

#### **General instructions**

## **A CAUTION**

#### Hot engine and/or hot exhaust system

Risk of burn injury

• Allow engine and exhaust system to cool before starting work.

#### **ATTENTION**

#### Vehicle not securely propped

Risk of damage to parts if vehicle topples

• Prop the vehicle securely.

### **A WARNING**

#### Children and pets in the working area

Injury to persons

• Keep children and pets away from the working area.

### **A CAUTION**

#### Wearing jewellery during work

Risk of injury by snagging or electrical short circuit

· Remove all items of personal jewellery (rings, chains, wristwatch, etc.) before starting work.

# **NOTICE**

Once the retrofit kit has been installed by the workshop, these installation instructions must be handed over to the customer.

Make sure that these installation instructions accompany the retrofit kit when it is passed on to a third party.


# 77 49 105 Installing the side bag holder



Two-up mode with mounted side bags is  ${f not}$  permitted

Additional work: 46 52 510 Mounting and dismounting the rear-wheel stand with special tools (for motorbikes without a centre stand)


1



### ► Preparing rear-wheel cover

- Remove screws (1).
- Remove plug (2).

2



### Installing left and right side bag holder

- Align side bag holder (1) with washers (2) and bush (3).
- Install screw (4).

Tightening torques			
Side bag holder to frame			
M8×45	23 Nm		

• Install screw (5).

Tightening torques	;		
Side bag holder to frame			
M8×30	23 Nm		

• Install holder on right in the same way.

3

### ► Final inspection of completed work

- Ensure the following:
- The objective of the completed work was achieved.

- All operating fluids have been filled in and the fluids are at the correct fill level.
- All loosened screw connections have been retightened correctly.
- The fuel system is free of leaks.
- The lighting and signal system is functional and the vehicle is roadworthy.
- The brake pads of the front and rear wheel brakes are resting against the brake disks.

### **▷** Function test, engine start suppression

#### Check

- Shift the transmission to idle position.
- Switch on the ignition.
- » Neutral indicator light "N" lights up.
- Select a gear.
- » Neutral indicator light "N" goes out.
- Operate the starter motor switch.
- » Starter does not operate.
- Extend the side stand.
- Pull the clutch lever.
- Operate the starter motor switch.
- » Starter does **not** operate.
- Retract the side stand.
- Operate the starter motor switch when the clutch is pulled.
- » Starter operates.

#### Result

Not all test steps completed successfully.

#### Measure

 Check the appropriate parts with the BMW Motorrad diagnostic system.

◁